

APPLICATION

OF

ERIC T. BAX

CHARLESS C. FOWLKES

LOUIS CISNERO, JR.

FOR

UNITED STATES LETTERS PATENT

ON

TECHNIQUE FOR EXTRACTING DATA FROM STRUCTURED DOCUMENTS

Docket: INFOS 45077

Drawings: 2 Sheets of Drawings

Attorneys
Sidley & Austin
555 West Fifth Street, 40th Floor
Los Angeles, California 90013-1010
Telephone: (213) 896-6663
Facsimile: (213) 896-6600

CERTIFICATE OF MAILING BY "EXPRESS MAIL"

"EXPRESS MAIL" MAILING LABEL No. EL 773912047 US

DATE OF DEPOSIT: NOVEMBER 30, 2000

I HEREBY CERTIFY THAT THIS PAPER OR FEE IS BEING DEPOSITED WITH THE UNITED STATES POSTAL SERVICE "EXPRESS MAIL POST OFFICE TO ADDRESSEE" SERVICE UNDER 37 CFR 1.10 ON THE DATE INDICATED ABOVE AND IS ADDRESSED TO BOX PATENT APPLICATION, ASSISTANT COMMISSIONER FOR PATENTS, WASHINGTON, DC 20231

ANN WEISS

(TYPED OR PRINTED NAME OF PERSON MAILING PAPER OR FEE) •

(SIGNATURE OF PERSON MAILING PAPER OR FEE)

TECHNIQUE FOR EXTRACTING DATA FROM STRUCTURED DOCUMENTS

CROSS-REFERENCE TO RELATED APPLICATIONS

This invention claims the benefit of Provisional Application Serial No. 60/195,556, filed
5 April 6, 2000. The contents of the application are incorporated by reference.

BACKGROUND OF THE INVENTION

1. FIELD OF THE INVENTION

This invention relates in general to data extraction process, and, in particular, to
extracting data from structured documents.

10 2. DESCRIPTION OF RELATED ART

With the fast growing popularity of the Internet and the World Wide Web ("WWW"),
there is a growing demand for a technique of extracting information from different web sites, and
storing the extracted information in a standard format. For example, a computer user may be
interested in gathering information from the WWW about cars, luggage, or travel destinations.
15 The user may wish to store this information in a user-defined format that allows the user to
compare the attributes of each subject.

To illustrate, assume that a user is interested in gathering information about cars from
several car-related web sites. More specifically, assume that the user is interested in gathering
information on individual cars, including the manufacturer, the model, the year, the color, and the
20 price.

Traditional techniques for solving this information gathering problem are typically based
on knowledge of the structure used to arrange data within each specific web site. (The structure
used to arrange the data within a page is commonly referred to as the syntax of the page.) These
techniques require prior determination of the syntax of each page and storage of syntax
25 information about each page in a data storage device, such as a database.

When gathering information about a subject from a particular page, the traditional

techniques identify the attributes of the subject by comparing the structure of the page with the stored structure information. When there is a match, the traditional technique returns the attribute value to the user.

These traditional techniques are limited because they can only gather attribute values from a page when they know the syntax of a page. To put it differently, the traditional techniques can only gather attribute values when the syntax of a page has been previously determined and stored. Accordingly, traditional techniques are generally incapable of gathering information from redesigned or restructured web-pages or from new web pages. The traditional technique lacks syntax information about these pages. For both the redesigned or restructured web pages and the new web pages, the traditional techniques require effort and resources to determine and store information about their syntax before gathering attribute values. Determining the syntax can be time-consuming, and a large amount of storage space may be needed to store the syntax information.

Thus, there is a need in the art for an improved technique of extracting information from any web-pages and any other structured documents.

SUMMARY OF THE INVENTION

To overcome the limitations in the prior art described above, and to overcome other limitations that will become apparent upon reading and understanding the present specification, the present invention discloses a technique for extracting data from a file.

In accordance with the present invention, a request to extract one or more data records from the file is received. The data records within the file are identified, without using prior knowledge of a structure of the file. The data records are then extracted.

BRIEF DESCRIPTION OF THE DRAWINGS

Referring now to the drawings in which like reference numbers represent corresponding parts throughout:

FIG. 1 schematically illustrates the hardware environment of a preferred embodiment of the present invention; and

FIG. 2 is a flowchart that illustrates the steps performed by the schematron system in

accordance with present invention.

DETAILED DESCRIPTION

In the following description, reference is made to the accompanying drawings which form a part hereof, and in which is shown by way of illustration, a specific embodiment in which the invention may be practiced. It is to be understood that other embodiments may be utilized as structural changes may be made without departing from the scope of the present invention.

Overview

The present invention, referred to herein as the schematron system, extracts data records from structured text, such as a web page or any file that contains text. Each data record contains attribute values that correspond to a single item. For example, a data record may contain the model, make, and color of a car or the size and price of a shoe.

The schematron system can extract record data without prior knowledge of the structure of the text. The schematron system deduces the structure of the text by using information about the attributes and knowledge of candidate structures. Both the information about the attributes and the knowledge of candidate structures are specified by the user. For the schematron system implementation described herein, user-friendly programs have been developed to specify attribute information and candidate structures in the course of providing initial input to the schematron system. A set of html-related candidate structures is provided with the implementation. The schematron system can store the attribute information and the knowledge of candidate structures in random access memory or in a data storage device.

The information about the attributes is called ontology. The ontology includes a specified set of possible labels for each attribute and a specified set of possible values for each attribute. For example, for the subject car and the attribute maker, the attribute labels may include maker and manufacturer. The possible attribute values may include BMW and Mercedes-Benz. The attribute information may also contain synonyms for possible attribute values, such as beamer for BMW or merc for Mercedes-Benz.

The knowledge of candidate structures is encoded as specified methods to partition a

region of text into a set of subregions. There are two types of candidate structures: (1) structures to locate the region of text that contains record data, and (2) structures to partition a region of text that contains record data into regions, wherein each region contains data for a single record.

5 In a typical data gathering scenario, the schematron system receives information about where to extract the record data from. The information may include a file name, a pathname, or a pointer to an array of characters representing a web-page or other document. The schematron system may receive this information from a user or from another application.

10 Using the received information, the schematron system accesses the document and searches for text that represents labels or values of each attribute. The schematron system uses locations and patterns of such text to deduce the region of record data within the document and to segment that region into regions of text that each contain data for a single record. Within each record region, for each attribute, the schematron system uses the results of the search for attribute values to determine the most likely location of text representing a
15 value for the attribute. Then the schematron system extracts the attribute values in each record region to form a record for each region. As a result, a set of records is extracted from the document.

20 In brief, the schematron system uses the knowledge that it contains about the attributes to identify the attribute labels and the attribute values within the text; to segment the text into records; and to extract attribute values for each record. Therefore, unlike conventional techniques, the schematron system is not required to have prior knowledge of the syntax of the document before extracting data from the document. Instead, the schematron system learns about the syntax (structure of the text) by determining the semantics (meaning of the words and symbols within the text).

25 Hardware

FIG. 1 is an exemplary hardware environment used to implement preferred embodiments of the invention. Embodiments of the present invention are implemented using a computer 100, which generally comprises a processor 102, random access memory (RAM) 104, data storage devices 106 (e.g., hard drive, floppy, and/or CD-ROM disc drives, etc.),

data communication devices 108 (e.g., modems, network interfaces, etc.), monitor 110 (e.g., CRT, LCD display, etc.), mouse pointing devices 112, and keyboard 114. It is envisioned that, attached to the computer 100 may be other devices such as a local area network (LAN) or wide area network (WAN), a video card, bus interface, printers, etc. The computer 100
5 operates under the control of an operating system 116 stored in the memory to present data to the user on the monitor 110 and to accept and process commands from the user via the keyboard 114 and mouse device 112. Those skilled in the art will recognize that any combination of the above components, or any number of different components, peripherals, and other devices, may be used with the computer 100.

10 The present invention is preferably implemented in one or more computer programs or applications (hereinafter referred to as the schematron system), which are depicted as block 118. The operating system 116 controls the execution of the schematron system 118. Under the control of the operating system 116, the schematron system 118 is loaded from the data storage device 106, and/or remote devices into the memory 104 of the computer for use
15 during actual operations. Generally, the operating system 116 and the schematron system 118 are tangibly embodied in and/or readable from a device, carrier, or media, and/or remote devices coupled to the computer 100 with the data communication device 108.

Those skilled in the art will recognize that the exemplary hardware environment illustrated in FIG. 1 is not intended to limit the present invention. Indeed those skilled in the
20 art will recognize that other alternative hardware environments may be used without departing from the scope of the present invention.

Data Extraction Process

The schematron system data performs the following steps. First, the text of a document (e.g., a web page or other file) is examined to determine possible sites of attribute
25 labels and values. Based on this examination, the schematron system locates a region of interest. A region of interest is defined as an area of the document that is likely to contain a requested record data. Next, the schematron system segments the region of interest into a sequence of record regions. Each record region is likely to contain data for a single record. Finally, the schematron system extracts attribute values from each record region, forming a

sequence of records.

Prior knowledge of ontology is represented in the schematron system by attribute label and value recognizers, known as word scorers. Attribute labels are text that may label attribute values, (e.g., possible labels for age include "age" and "years of age.") Some word scorers contain lists of words and phrases. For example, a word scorer for the label of a price attribute may contain the words "price," "cost," and "amount." Other word scorers use algorithms to detect classes of expressions. For example, a word scorer for price attribute values may detect the following patterns in text, where the word "(number)" refers to any number: \$(number), USD (number).

Prior knowledge of candidate structures is represented in the schematron system by routines that take a region of text as input and return a set of subregions as output, called region partitioners. The region partitioners used to focus on the region of interest produce a set of subregions such that, for some documents, one of the subregions contains the record data. The region partitioners used to segment the region of interest into record regions produce a set of subregions such that, for some documents, each subregion contains the attribute data for a single record.

In an embodiment of the present invention, the schematron system implementation reads data from html files and stores the data as records in xml files. Of course, the schematron system could read data from other types of files, such as xml files, database files, spreadsheet files, or word processor files, and the schematron system could store the extracted records using other formats, such as html files, database files, spreadsheet files, word processor files, or custom formats, without exceeding the scope of this invention.

FIG. 2 is a flowchart illustrating the steps performed to extract data records from structured text in accordance with the present invention. Block 202 represents the schematron system 118 reading text from a file that contains structured text.

The schematron system then cleans the text, as represented by block 204. Cleaning involves separating tags (e.g., html tags, xml tags, etc.) from other text, so that the schematron system can recognize the tags and text as separate words in subsequent steps. A tag is a command inserted into a document that specifies the manner in which the document, or portion of the document, should be formatted. Exemplary text may include:

“<command>other text</command>,” wherein <command> and </command> are the tags.

Separating tags from other text consists of adding a single space before each “<” character and after each “>” character. For example, the text “<td>info</td>” becomes “<td> info </td>.” Also, any space after a “<” character or before a “>” character is deleted, in order to compact tags. Finally, each html space, “ ,” is converted into five text spaces, “ ”.

Block 206 represents the schematron system chopping the text. Chopping involves converting the text into a word list. For example, the schematron system converts the text “quiet hours\tkitten naps--” into the following word list: “quiet”, “hours”, “kitten”, and “naps--”. It is noted that the schematron system interprets “naps--” as a single word. Word separators such as space, tab, and end-of-line characters are different from words, and thus, are absent from the word list. In the above example, “\t” is a tab character, and hence, “\t” is absent from the word list. Each subsequent step in this flowchart is based on the words contained in the word list.

Block 208 represents the schematron system performing the scoring process. During the scoring process, the schematron system recognizes the positions of attribute labels and values in the word list. For each attribute, the schematron system has two word scorers -- a label scorer and a value scorer.

Each word scorer is a module that receives input, such as the word list and a specified position in the word list. For each word, the scorer returns an output value that is associated with the position of that word on the word list. This output value ranges from zero to one. The output value is an estimate of the probability that the word at the specified position begins text in the word list which contains an attribute label or an attribute value.

The output value (or score) may depend on the context of the word within the word list. As an example, when analyzing the word list “for sale: Alpha Romeo,” a scorer for automobile manufacturers may return the output value of one for the word “Alpha.” On the other hand, when analyzing the word list “Alpha Beta Gamma,” the scorer for automobile manufacturers may return the output value of zero for the word “Alpha.”

To create a scorecard for the word list, the schematron system provides output values for each word position in the word list. More specifically, each attribute label scorer

provides an output value and each attribute value scorer provides an output value. In the scorecard, there are values corresponding to each member of the set:

$$\{\text{positions in word list}\} \times \{\text{attributes}\} \times \{\text{label, value}\}$$

Block 210 represents the schematron system focusing. During the focus process, the schematron system identifies a region of interest of the word list that contains text corresponding to the data to be extracted. The schematron system has a list of focus region partitioners. Each focus region partitioner is a module that receives, as input, a region of the word list. The focus region partitioner returns, as output, a set of subregions. The steps of the focus process are shown below:

(1) Initially, assign the candidate region to be the region consisting of the entire word list.

(2) For each focus region partitioner:

(a) Apply the partitioner to the candidate region to produce a set of subregions.

(b) If there is more than one subregion in the set, then assign the partitioner the grade:

grade = (sum of all attribute label and attribute value scores in subregion with maximum of this sum)

- (average over subregions of sum of all label and value scores in subregion).

(3) If no partitioner produced a set of subregions with more than one subregion, then return the candidate region as the region of interest and stop.

(4) Assign the candidate region to be the highest-scoring subregion in the set of subregions produced by the partitioner with the highest grade in the most

recent step (2).

(5) Go to step (2).

The focus process is iterative so that the region of interest can be discovered even if it is nested, for example, a table within a table. It is noted that no single focus partitioner needs to be successful for all documents, since all partitioners are tried on each document, and the most successful partitioner or sequence of partitioners is used to identify the region of interest.

Block 212 represents the schematron system segmenting the region of interest. Segmenting involves partitioning the region of interest into record regions that each contain text corresponding to a single record. The schematron system has a list of segment region partitioners. Each segment region partitioner is a module that receives, as input, a region of the word list, and returns, as output, a set of subregions. The segment process is as follows:

(1) For each segment region partitioner:

(a) Apply the partitioner to the region of interest to produce a set of subregions.

(b) If there are no subregions in the set, then assign the partitioner an extremely high grade, representing infinity. (Low grades are favored in segmenting.) If there is at least one subregion in the set, then assign the partitioner a grade which is the average of the subregion grades determined by the process:

(i) Form an array with two entries corresponding to each attribute -- a label entry and a value entry.

(ii) Fill in the array by summing the scores corresponding to entries over all words in the subregion.

(iii) The subregion grade is the sum of the squares of the differences between the entries and the value one.

(2) Return as the set of record regions the set of subregions produced by the partitioner with the lowest grade.

- 5 As with the focus region partitioners, no single segment region partitioner needs to be successful for all documents, since all segment partitioners are tried for each document, and the most successful one is used.

Block 214 represents the schematron system performing an extracting process. The extracting process involves determining attribute values for records based on the text in
10 record regions. The schematron system has an extractor for each attribute. Each extractor is a module that receives, as input, the word list and a specified position in the word list and returns, as output, a value for the corresponding attribute. The returned value may depend on context within the word list. For example, when the input is the third position, and the word list is "for sale: Alpha Romeo in good condition, . . . ", an extractor for the maker attribute of
15 car items may return "Alpha Romeo."

An extractor is not required to return text. For example, an extractor of dollar amounts may return the numerical value -17.63 when the input is the second position and word list is "total: -\$17.63." The returned value may also be a special "null" value indicating that the extractor was unsuccessful.

20 The schematron system applies the following extraction process to each record region. For each attribute, the schematron system identifies the word position in the record region with the highest value score for the attribute. When two or more word positions have the exact same value, the earliest of the highest-scoring positions is chosen.

When schematron system extracts an attribute value, the attribute value is added to
25 the record. When the schematron system extracts a "null" value, the schematron system records in the record that no value has been extracted for the attribute. When a value is extracted for at least one attribute, then the resulting record is included in the set of records.

Block 216 represents the schematron system writing the set of records to a file, such as an xml file. The schematron system has an item name and a set of attribute names. The item name indicates the type of item corresponding to each record, and the attribute names indicate attributes. For example, a schematron system that extracts data from each record corresponding to a car may have item name "car" and attribute names "make", "model", "year", "color", and "price." Each record has the following format:

```
<(item name) (attribute name)="(attribute value)" (attribute name)="(attribute value)"/>
```

If an attribute has no value in a record, then the corresponding name/value pair is not written into the file. The file consists of a list of records (e.g., xml records), one on each line.

Schematron System Data and Routines

The schematron system is specified by data and routines. The data includes the item name, the attribute names, and data, such as word lists, used by routines. The routines include: label word scorers, value word scorers, extractors, focus region partitioners, and segment region partitioners.

A schematron system designer can choose and configure routines that are executed by the schematron system. The designer also has the option of implementing new routines and including them in the schematron system.

In an embodiment of the present invention, the schematron system includes the following routines:

Word Scorer Routine

The input of the word scorer routine includes a word list and a position of a word in the word list as inputs. The output of the word scorer routine includes a number from zero to one. The output is an estimate of the probability that the word at the specified position in the word list begins an attribute label or an attribute value for a particular attribute.

There are several types of word scorer routines, including a phrase word scorer, a dollar

amount word scorer, and a dollar amount range word scorer. The phrase word scorer contains a list of phrases. When the words beginning at the specified position of the word list match a phrase in the phrase list, then the scorer returns an output value of one. otherwise, the scorer returns an output value of zero.

- 5 The dollar amount word scorer (referred to herein as the amount scorer) returns an output value of one when the word in the specified position begins with an expression that matches any one of the following expressions: "\$ (number)", "\$ (number)", or "-\$(number)." The word "number" corresponds to any number. The dollar amount word scorer returns an output value of one half if the specified position in the word list contains a number.
- 10 Otherwise, the dollar amount word scorer returns an output value of zero.

- The dollar amount range word scorer (referred to herein as the range amount scorer) contains three values: low, medium, and high. When the amount scorer returns an output value of zero, the range amount scorer returns an output value of zero. The range amount scorer returns the following: a value of zero for amounts less than low; a value that varies
- 15 linearly from one tenth to one for amounts that range from low to medium; a value that varies linearly from one to one tenth for amounts from medium to high; and a value of zero for amounts greater than high.

- When an expression contains a dollar sign, the amount score is returned. Otherwise, one tenth of the amount score is returned. By favoring some amounts over others, the range
- 20 amount scorer can differentiate among prices within a single record, and it can differentiate among numbers when prices are not labelled by dollar signs. For example, suppose a schematron system reads new car data from html documents. When the prices in the html document lack dollar signs, the dollar amount word scorer scores the year of the car as high as the price. However, a dollar amount range word scorer, containing values such as low =
- 25 2000, medium = 20,000, and high = 200,000, scores typical new car prices higher than current years.

Extractors

The input of an extractor routine is a word list and a position of the word in the word list. The output is an attribute value or a "null" value. Two types of extractor routines are

phrase extractor and dollar amount extractor.

The phrase extractor contains a list of phrases. When the words beginning at the specified position of the word list match a phrase in the list, the extractor routine returns the earliest such phrase in its list. Otherwise, the extractor returns "null".

- 5 The dollar amount extractor routine returns a numerical value that corresponds to the amount displayed in the expressions for which the dollar amount word scorer returns positive values. Otherwise, the extractor returns "null" for other expressions.

Region Partitioners

- 10 The input to region partitioner routines includes a region of the word list. The output is a set of subregions. The types of region partitioners, include the balanced tag region partitioner, the balanced prefix tag region partitioner, and the snip word region partitioner.

- 15 Balanced tag region partitioner routines are applied to partitions that use balanced "open" and "close" tags, which are treated like parentheses. If the tags are not balanced, then the routine returns the entire region as the only subregion. If the entire region is surrounded by a balanced pair of open and close tags, then the routine removes the tags and partitions the remainder of the region. Once the routine has stripped away the initial and final open-close tags, the routine uses the top-level remaining open-close tags as the basis for partitioning.

- 20 The routine partitions into regions according to top-level tags. The routine makes a subregion of any text before the first open tag; a subregion of all text from the first open tag to its balanced close tag; a subregion of any text before the next open tag; a subregion from the next open tag to its balanced close tag; and so forth.

An example of a balanced tag region partitioner with "<table>" as the open tag, with "</table>" as the close tag, and with an input region is shown in Example 1 below:

Example 1

- 25 <table>
before
 <table>
 <tr> <td>a</td> <td>b</td> </tr>


```
| <td>
    <table>
| <td>e</td> <td>f</td> </tr>
| <td>g</td> <td>h</td> </tr>
5  </table>
    </td> </tr>

|  |

|  |

|  |

```

```
| <td>i</td> </tr>
</table>

|  |

```

10 -----
(5) after

The balanced prefix tag region partitioner routine is similar to the balanced tag region partitioner region. The difference between the two routines is that the balanced prefix tag region partitioner routine treats any word with the specified "open prefix" as an open tag.

15 The balanced prefix tag routine also treats any word with the specified "close prefix" as a close tag. This treatment of prefixes is useful for html tags in which the open tag may be a single word or may be simply the first word of a tag that includes property specifications. For example, an opening table tag may have the form "<table>" or the form "<table align=left>". In the first example, the first word is "<table>". In the second example, the first word is

20 "<table". Using "<table" as a prefix for the open tag captures both cases.

The snip word region partitioner routine partitions a region into subregions that end with the specified "snip" word or with the end of the region. An example of a snip word region partitioner with a snip word of "" and with an input region is shown in Example 3 below:

25 **Example 3**

```

<ul>
<li> Red 1960 Volvo $20000
<li> 1962 Green Cadillac $30000

```


 \$300 1971 VW Bug White

The snip word region partitioner routine returns the subregions shown in Example 4 below:

5 **Example 4**

(1)

(2) Red 1960 Volvo \$20000

10 (3) 1962 Green Cadillac \$30000

(4) \$300 1971 VW Bug White

The snip word prefix region partitioner routine is similar to the snip word region partitioner. The difference between the two routines is that the snip word prefix region partitioner treats any word with a specified "snip prefix" as a snip word.

An example of the manner in which the schematron system operates on an exemplary input file is shown below. The following example schematron system extracts data in which each record corresponds to a car.

The exemplary schematron is shown in Example 5 below:

20 **Example 5**

item name -- car

attribute list

attribute

name -- make

label word scorer -- phrase word scorer based on a list of make labels

value word scorer -- phrase word scorer based on a list of makes

extractor -- phrase extractor based on a list of makes

5 attribute

name -- model

label word scorer -- phrase word scorer based on a list of model labels

value word scorer -- phrase word scorer based on a list of models

10 extractor -- phrase extractor based on a list of models

attribute

name -- year

label word scorer -- phrase word scorer based on a list of year labels

15 value word scorer -- phrase word scorer based on a list of years

extractor -- phrase extractor based on a list of years

attribute

[illegible][illegible][illegible][illegible][illegible][illegible][illegible][illegible][illegible][illegible][illegible][illegible][illegible][illegible][illegible]

segment region partitioner – html list item partitioner

segment region partitioner – html definition term partitioner

segment region partitioner – html definition partitioner

segment region partitioner – html line break partitioner

5 In the schematron shown in Example 5, the focus region partitioners are particular examples of balanced prefix tag region partitioners. Table 1 shows the partitioners and tags.

TABLE 1

	partitioner	open prefix	close prefix
	-----	-----	-----
10	html table	<table	</table
	html unordered list	<ul	</ul
	html ordered list	<ol	</ol

15 In the schematron shown in Example 5, the segment region partitioners are particular examples of snip word prefix region partitioners. Table 2 shows the partitioners and snip prefixes

TABLE 2

	partitioner	snip prefix
	-----	-----
	html table row	<tr
20	html list item	<li
	html definition term	<dt

html definition <dd
html line break <br

An example of the manner in which the schematron system extracts data from an exemplary text file is discussed below.

- 5 Example 6 represents an exemplary text file. In Example 6, the bolded portions represent text that is discussed herein. It is noted that the portions are bolded for discussions purposes only.

Example 6

<html>
10 <head> <title>cars example document</title> </head>
 <body>
 <table border=1>
 <tr> <td>CARS!</td> <td>CARS!</td> <td>CARS!</td> </tr>
 <tr> <td>LIKE NEW</td> <td>GREAT QUALITY</td> <td>GREAT PRICES</td> </tr>
15 </table>

 Shop with us online.

 Low prices.
20 Shop 24 x 7.
 No pesky salesmen!

 <table border=1>
 <tr> <th>Year</th> <th>Make</th> <th>Model</th> <th>Price</th> <th>Info</th>
25 </tr>
 <tr> <td>1998</td> <td>Acura</td> <td>Integra</td> <td>\$10000</td> <td>Color:
 Blue</td> </tr>
 <tr> <td>1995</td> <td>Jeep</td> <td>Cherokee</td> <td>\$8500</td> <td>Color:

```

Green</td> </tr>
<tr> <td>1990</td> <td>Toyota</td> <td>4Runner</td> <td>7500</td> <td>Miles:
80000</td> </tr>
</table>
5 <br>
Call now: 1-800-BUY-A-CAR!
</body>
</html>

```

- 10 First, the schematron system reads the text file shown in Example 6. Second, the schematron system cleans the text file. More specifically, the schematron system uses spaces to separate the html tags from nearby text. For example, "<td>1998</td>" in the original text becomes " <td> 1998 </td> " in the cleaned text. The cleaning causes "1998" to become a separate word when the schematron system chops the text into words. An example of a
- 15 cleaned file is shown in Example 7. In Example 7, the bolded portions of the cleaned file represent text that is discussed herein. It is noted that the portions are bolded for discussions purposes only.

Example 7

```

<html>
20 <head> <title> cars example document </title> </head>
<body>
<table border=1>
<tr> <td> CARS! </td> <td> CARS! </td> <td> CARS! </td> </tr>
<tr> <td> LIKE NEW </td> <td> GREAT QUALITY </td> <td> GREAT PRICES
25 </td>
</tr>
</table>
<br>
Shop with us online.

```


 Low prices.

 Shop 24 x 7.

 No pesky salesmen!

5

<table border=1>

<tr> <th> Year </th> <th> Make </th> <th> Model </th> <th> Price </th>

<th> Info </th> </tr>

<tr> <td> 1998 </td> <td> Acura </td> <td> Integra </td> <td> \$10000

10 </td> <td> Color: Blue </td> </tr>

<tr> <td> 1995 </td> <td> Jeep </td> <td> Cherokee </td> <td> \$8500

</td> <td> Color: Green </td> </tr>

<tr> <td> 1990 </td> <td> Toyota </td> <td> 4Runner </td> <td> 7500

</td> <td> Miles: 80000 </td> </tr>

15 </table>

Call now: 1-800-BUY-A-CAR!

</body>

</html>

20

In the third step, the schematron system chops the data into words. Chopping involves converting the text into a word list. For example, the schematron system converts the text "cars example document" (see Example 7) into the following word list: "cars", "example", and "document." Example 8 shows an exemplary word list.

25 Example 8

0 <html>

1 <head>

2 <title>

3 cars

4 example
 5 document
 6 </title>
 7 </head>
 5 8 <body>
 9 <table
 10 border=1>
 11 <tr>
 12 <td>
 10 13 CARS!
 14 </td>
 15 <td>
 16 CARS!
 17 </td>
 15 18 <td>
 19 CARS!
 20 </td>
 21 </tr>
 22 <tr>
 20 23 <td>
 24 LIKE
 25 NEW

:
:

25 In the fourth step, the schematron system scores the words and constructs a score
 card. Each score is a value between zero and one. This value is an estimate of the
 probability that a word, at a specified position in the word list, begins text in the word list
 which contains an attribute label or an attribute value. Example 9 shows an exemplary score
 card. In Example 9, the scores are listed in the following order: make, model, year, color,
 30 price.

In Example 9, the bolded portions represent text that is discussed herein. It is noted that the portions are bolded for discussions purposes only.

Example 9

:
5 :
Make: label -- 1.0 0.0 0.0 0.0 0.0 value -- 0.0 0.0 0.0 0.0 0.0
</th>: label -- 0.0 0.0 0.0 0.0 0.0 value -- 0.0 0.0 0.0 0.0 0.0
<th>: label -- 0.0 0.0 0.0 0.0 0.0 value -- 0.0 0.0 0.0 0.0 0.0
Model: label -- 0.0 1.0 0.0 0.0 0.0 value -- 0.0 0.0 0.0 0.0 0.0
10 :
:
1998: label -- 0.0 0.0 0.0 0.0 0.0 **value -- 0.0 0.0 1.0 0.0 0.019**
</td>: label -- 0.0 0.0 0.0 0.0 0.0 value -- 0.0 0.0 0.0 0.0 0.0
<td>: label -- 0.0 0.0 0.0 0.0 0.0 value -- 0.0 0.0 0.0 0.0 0.0
15 **Acura:** label -- 0.0 0.0 0.0 0.0 0.0 value -- 1.0 0.0 0.0 0.0 0.0
</td>: label -- 0.0 0.0 0.0 0.0 0.0 value -- 0.0 0.0 0.0 0.0 0.0
<td>: label -- 0.0 0.0 0.0 0.0 0.0 value -- 0.0 0.0 0.0 0.0 0.0
Integra: label -- 0.0 0.0 0.0 0.0 0.0 value -- 0.0 1.0 0.0 0.0 0.0
</td>: label -- 0.0 0.0 0.0 0.0 0.0 value -- 0.0 0.0 0.0 0.0 0.0
20 <td>: label -- 0.0 0.0 0.0 0.0 0.0 value -- 0.0 0.0 0.0 0.0 0.0
\$10000: label -- 0.0 0.0 0.0 0.0 0.0 **value -- 0.0 0.0 0.0 0.0 0.690**
</td>: label -- 0.0 0.0 0.0 0.0 0.0 value -- 0.0 0.0 0.0 0.0 0.0
<td>: label -- 0.0 0.0 0.0 0.0 0.0 value -- 0.0 0.0 0.0 0.0 0.0
Color:: label -- 0.0 0.0 0.0 1.0 0.0 value -- 0.0 0.0 0.0 0.0 0.0
25 Blue: label -- 0.0 0.0 0.0 0.0 0.0 value -- 0.0 0.0 0.0 1.0 0.0
:
:
1990: label -- 0.0 0.0 0.0 0.0 0.0 value -- 0.0 0.0 1.0 0.0 0.019
</td>: label -- 0.0 0.0 0.0 0.0 0.0 value -- 0.0 0.0 0.0 0.0 0.0

```

<td>: label -- 0.0 0.0 0.0 0.0 0.0 value -- 0.0 0.0 0.0 0.0 0.0
Toyota: label -- 0.0 0.0 0.0 0.0 0.0 value -- 1.0 0.0 0.0 0.0 0.0
</td>: label -- 0.0 0.0 0.0 0.0 0.0 value -- 0.0 0.0 0.0 0.0 0.0
<td>: label -- 0.0 0.0 0.0 0.0 0.0 value -- 0.0 0.0 0.0 0.0 0.0
5  4Runner: label -- 0.0 0.0 0.0 0.0 0.0 value -- 0.0 1.0 0.0 0.0 0.0
</td>: label -- 0.0 0.0 0.0 0.0 0.0 value -- 0.0 0.0 0.0 0.0 0.0
<td>: label -- 0.0 0.0 0.0 0.0 0.0 value -- 0.0 0.0 0.0 0.0 0.0
7500: label -- 0.0 0.0 0.0 0.0 0.0 value -- 0.0 0.0 0.0 0.0 0.053
</td>: label -- 0.0 0.0 0.0 0.0 0.0 value -- 0.0 0.0 0.0 0.0 0.0
10 <td>: label -- 0.0 0.0 0.0 0.0 0.0 value -- 0.0 0.0 0.0 0.0 0.0
Miles:: label -- 0.0 0.0 0.0 0.0 0.0 value -- 0.0 0.0 0.0 0.0 0.0
80000: label -- 0.0 0.0 0.0 0.0 0.0 value -- 0.0 0.0 0.0 0.0 0.031
:
:

```

15 It is noted that for the Acura Integra in Example 9, the schematron system recognizes the year, 1998, as a possible price. The price score for the year is 0.19. However, the actual price, \$10,000, outscores the year. The price score for the actual price is 0.690. This higher price score is based on at least two conditions. First, the actual price contains a dollar sign, "\$". Second, the value of the price is within the specified range of the price word scorer. As shown in Example 5, the specified range for price is: low = 500.0; medium = 15000.0; and high = 100000.0.

20 A similar situation occurs for the Toyota 4Runner. However, the Toyota price of 7500 lacks a dollar sign. Other numeric values for Toyota include, the mileage, 80000, and the year, 1990. Still, the actual price score is higher than the scores for both the year and the mileage – 0.053 for the actual price versus 0.019 for the year and 0.031 mileage.

25 In the fifth step, the schematron system performs the focus process. Specifically, the schematron system locates a region of interest of the word list by iteratively invoking all focus partitioners, and applying the focus partitioner with the highest grade, until all partitioners fail to produce multiple subregions. The grade is calculated using the following equation:

30

grade = (sum of all attribute label and attribute value scores in subregion with maximum of this sum)

- (average over subregions of sum of all label and value scores in subregion).

- 5 For the word list shown in Example 8, two iterations are required. For iteration 1, the candidate region of interest is the entire region. The grades and subregion sets produced by each focus partitioner are shown in Example 10.

Example 10

html table partitioner

10 grade: 14.743

subregions:

(1) <html> <head> <title> cars example document </title> </head> <body>

(2) <table border=1> <tr> <td> CARS! </td> <td> CARS! </td> <td> CARS! </td>

15 </tr> <tr> <td> LIKE NEW </td> <td> GREAT QUALITY </td> <td> GREAT PRICES

</td>

</tr> </table>

(3)
 Shop with us online. Low prices. Shop 24 x 7. No

20 pesky salesmen!

(4) <table border=1> <tr> <th> Year </th> <th> Make </th> <th> Model </th> <th>

Price </th> <th> Info </th> </tr> <tr> <td> 1998 </td> <td> Acura </td> <td>

Integra </td> <td> \$10000 </td> <td> Color: Blue </td> </tr> <tr> <td> 1995

25 </td> <td> Jeep </td> <td> Cherokee </td> <td> \$8500 </td> <td> Color: Green

</td> </tr> <tr> <td> 1990 </td> <td> Toyota </td> <td> 4Runner </td> <td> 7500

</td> <td> Miles: 80000 </td> </tr> </table>

(5)
 Call now: 1-800-BUY-A-CAR! </body> </html>

html unordered list partitioner

grade: 12.286

5 subregions:

(1) <html> <head> <title> cars example document </title> </head> <body> <table border=1> <tr> <td> CARS! </td> <td> CARS! </td> <td> CARS! </td> </tr> <tr> <td> LIKE NEW </td> <td> GREAT QUALITY </td> <td> GREAT PRICES </td> </tr> </table>
 Shop with us online.

10 -----

(2) Low prices. Shop 24 x 7. No pesky salesmen!

(3) <table border=1> <tr> <th> Year </th> <th> Make </th> <th> Model </th> <th> Price </th> <th> Info </th> </tr> <tr> <td> 1998 </td> <td> Acura </td> <td> Integra </td> <td> \$10000 </td> <td> Color: Blue </td> </tr> <tr> <td> 1995 </td> <td> Jeep </td> <td> Cherokee </td> <td> \$8500 </td> <td> Color: Green </td> </tr> <tr> <td> 1990 </td> <td> Toyota </td> <td> 4Runner </td> <td> 7500 </td> <td> Miles: 80000 </td> </tr> </table>
 Call now: 1-800-BUY-A-CAR! </body> </html>

20 In Example 10, the html table partitioner has the highest grade, 14.743. Accordingly, the html table partitioner is applied. The highest-scoring subregion in the resulting set is the subregion consisting of the table with data on individual cars - - subregion (4) - - so it becomes the candidate region. The html ordered list partitioner produces a single subregion, consisting of the entire region. The entire region is shown in Example 7. Therefore, the
25 region is not graded.

For iteration 2, the candidate region is shown in Example 11. The grades and subregion sets produced by each focus partitioner are as follows: the html table partitioner produces a single subregion, consisting of the entire region; the html unordered list

Color: Blue </td> </tr> <tr>

(4) <td> 1995 </td> <td> Jeep </td> <td> Cherokee </td> <td> \$8500 </td> <td>

Color: Green </td> </tr> <tr>

5

(5) <td> 1990 </td> <td> Toyota </td> <td> 4Runner </td> <td> 7500 </td> <td>

Miles: 80000 </td> </tr> </table>

html list item partitioner

10 grade: 38.041

subregions:

(1) <table border=1> <tr> <th> Year </th> <th> Make </th> <th> Model </th> <th>

Price </th> <th> Info </th> </tr> <tr> <td> 1998 </td> <td> Acura </td> <td>

Integra </td> <td> \$10000 </td> <td> Color: Blue </td> </tr> <tr> <td> 1995

15 </td> <td> Jeep </td> <td> Cherokee </td> <td> \$8500 </td> <td> Color: Green

</td> </tr> <tr> <td> 1990 </td> <td> Toyota </td> <td> 4Runner </td> <td> 7500

</td> <td> Miles: 80000 </td> </tr> </table>

html definition term partitioner

grade: 38.041

20 subregions:

(1) <table border=1> <tr> <th> Year </th> <th> Make </th> <th> Model </th> <th>

Price </th> <th> Info </th> </tr> <tr> <td> 1998 </td> <td> Acura </td> <td>

Integra </td> <td> \$10000 </td> <td> Color: Blue </td> </tr> <tr> <td> 1995

</td> <td> Jeep </td> <td> Cherokee </td> <td> \$8500 </td> <td> Color: Green

25 </td> </tr> <tr> <td> 1990 </td> <td> Toyota </td> <td> 4Runner </td> <td> 7500

</td> <td> Miles: 80000 </td> </tr> </table>

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80	81	82	83	84	85	86	87	88	89	90	91	92	93	94	95	96	97	98	99	100
1	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80	81	82	83	84	85	86	87	88	89	90	91	92	93	94	95	96	97	98	99	100
2	2	1	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80	81	82	83	84	85	86	87	88	89	90	91	92	93	94	95	96	97	98	99	100
3	3	2	1	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80	81	82	83	84	85	86	87	88	89	90	91	92	93	94	95	96	97	98	99	100
4	4	3	2	1	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80	81	82	83	84	85	86	87	88	89	90	91	92	93	94	95	96	97	98	99	100
5	5	4	3	2	1	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80																				

subregions:

5

15

subregions:

15

20

Accordingly, the html table row partitioner is applied to produce the record regions. It is noted that the other segment partitioners fail to partition the region of interest into multiple subregions.

The record regions are shown in Example 13.

25

(2)	Year	Make	Model	Price	Info
1	2014	Toyota	Camry	18,000	Good
2	2015	Honda	Civic	22,000	Good
3	2016	Ford	Fusion	25,000	Good
4	2017	Chrysler	Pacifica	30,000	Good
5	2018	Jeep	Wrangler	35,000	Good
6	2019	Subaru	Outback	40,000	Good
7	2020	Volvo	S60	45,000	Good
8	2021	BMW	3 Series	50,000	Good
9	2022	Mercedes	C-Class	55,000	Good
10	2023	Audi	A4	60,000	Good
11	2024	Porsche	911	75,000	Good
12	2025	Ferrari	488	90,000	Good
13	2026	Lamborghini	Huracan	100,000	Good
14	2027	Rolls Royce	Phantom	120,000	Good
15	2028	Bentley	Continental	130,000	Good
16	2029	Maybach	S-Class	140,000	Good
17	2030	Rolls Royce	Spectre	150,000	Good
18	2031	Mercedes	EQS	160,000	Good
19	2032	BMW	iX	170,000	Good
20	2033	Volvo	XC90	180,000	Good
21	2034	Subaru	Ascent	190,000	Good
22	2035	Jeep	Grand Cherokee	200,000	Good
23	2036	Ford	Expedition	210,000	Good
24	2037	Chrysler	Pacifica	220,000	Good
25	2038	Toyota	Sienna	230,000	Good
26	2039	Honda	Odyssey	240,000	Good
27	2040	Volvo	S90	250,000	Good
28	2041	BMW	7 Series	260,000	Good
29	2042	Mercedes	S-Class	270,000	Good
30	2043	Audi	A8	280,000	Good
31	2044	Porsche	Panamera	290,000	Good
32	2045	Ferrari	812	300,000	Good
33	2046	Lamborghini	Revuelto	310,000	Good
34	2047	Rolls Royce	Spectre	320,000	Good
35	2048	Bentley	Continental	330,000	Good
36	2049	Maybach	S-Class	340,000	Good
37	2050	Rolls Royce	Spectre	350,000	Good
38	2051	Mercedes	S-Class	360,000	Good
39	2052	BMW	7 Series	370,000	Good
40	2053	Volvo	S90	380,000	Good
41	2054	Subaru	Ascent	390,000	Good
42	2055	Jeep	Grand Cherokee	400,000	Good
43	2056	Ford	Expedition	410,000	Good
44	2057	Chrysler	Pacifica	420,000	Good
45	2058	Toyota	Sienna	430,000	Good
46	2059	Honda	Odyssey	440,000	Good
47	2060	Volvo	S90	450,000	Good
48	2061	BMW	7 Series	460,000	Good
49	2062	Mercedes	S-Class	470,000	Good
50	2063	Audi	A8	480,000	Good
51	2064	Porsche	Panamera	490,000	Good
52	2065	Ferrari	812	500,000	Good
53	2066	Lamborghini	Revuelto	510,000	Good
54	2067	Rolls Royce	Spectre	520,000	Good
55	2068	Bentley	Continental	530,000	Good
56	2069	Maybach	S-Class	540,000	Good
57	2070	Rolls Royce	Spectre	550,000	Good
58	2071	Mercedes	S-Class	560,000	Good
59	2072	BMW	7 Series	570,000	Good
60	2073	Volvo	S90	580,000	Good
61	2074	Subaru	Ascent	590,000	Good
62	2075	Jeep	Grand Cherokee	600,000	Good
63	2076	Ford	Expedition	610,000	Good
64	2077	Chrysler	Pacifica	620,000	Good
65	2078	Toyota	Sienna	630,000	Good
66	2079	Honda	Odyssey	640,000	Good
67	2080	Volvo	S90	650,0	

</th> </tr> <tr>

(3) <td> 1998 </td> <td> Acura </td> <td> Integra </td> <td> \$10000 </td> <td>
Color: Blue </td> </tr> <tr>

5

(4) <td> 1995 </td> <td> Jeep </td> <td> Cherokee </td> <td> \$8500 </td> <td>
Color: Green </td> </tr> <tr>

(5) <td> 1990 </td> <td> Toyota </td> <td> 4Runner </td> <td> 7500 </td> <td>

10 Miles: 80000 </td> </tr> </table>

The seventh step involves the schematron system applying the attribute extractors to the highest value-scoring positions within the record regions to extract attribute values, forming records.

An example of extracted records is shown below:

15

Acura Integra 1998 Blue 10000.0
Jeep Cherokee 1995 Green 8500.0
Toyota 4Runner 1990 null 7500.0

20

These extracted records were produced from record regions, (3), (4), and (5), shown in Example 13. The record regions (1) and (2) do not yield records because all the extractors fail to extract attribute values from these regions. It is also noted that a "null" value is recorded for the color of the Toyota 4Runner, because no color is extracted from the record region.

Finally, the schematron system writes the output to a file, as shown below:

25

```
<car make="Acura" model="Integra" year="1998" color="Blue"  
price="10000.0"/>  
<car make="Jeep" model="Cherokee" year="1995" color="Green"
```


